# ZEBRA® P100i CARD PRINTER





## THE MOST FEATURE-RICH AND AFFORDABLE CARD PRINTER IN ITS CLASS

Zebra's single-feed, single-sided P100; colour card printer lets you create individual customised cards on demand.

Easy to use and budget-friendly, it helps you put personalised cards in the hands of cardholders in just moments.

The P100i saves time and effort if you often print a variety of card types. Its three built-in storage bays keep up to 100 cards on hand, clean, and ready to use. The printer's small footprint and light weight make it ideal for use in a variety of locations. Optional features such as magnetic stripe encoding and smart card encoding make this a truly flexible and powerful printer.

### **KEY FEATURES**

- · Single sided, full colour or monochrome printing
- · Magnetic encoding
- · Smart-card encoding
- ATM style Card Sense<sup>™</sup> single-card feed
- · Ethernet connectivity

## **IDEAL FOR:**

- · Customised bank/ATM cards
- Employee ID and building access control cards
- · Student and faculty ID's
- · Hotel and event cards
- · Membership cards
- · Personalised gift or loyalty cards
- · Transit and recreation passes

## **GET THE MOST OUT OF YOUR PRINTERS, USE GENUINE ZEBRA SUPPLIES!**

Load-N-Go™ ribbon cartridge with integrated card cleaning roller for easy ribbon replacement

- ι Series intelligent ribbon technology
- · Available in full colour or monochrome black, blue, green, gold, red, silver and white



For more information, visit www.zebracard.com



## SPECIFICATIONS AT A GLANCE\*

#### **GENERAL SPECIFICATIONS**

- · Single-sided printing full colour or monochrome
- ATM style CardSense<sup>™</sup> single-card feed
- Load-N-Go™ drop-in ribbon cartridge
- 16-character LCD display for printer status and error reporting messages
- · Windows® drivers for 2000, XP, and Vista compatible
- 100-card covered holder
- · Two year printer warranty
- Two year (unlimited passes) original printhead warranty

#### **PRINTING**

- Colour dye sublimation or monochrome thermal transfer printing
- · Single-card feed 6 seconds per card monochrome
- Single-card feed 35 seconds per card full colour (YMCKO)
- 300 dpi (11.8 dots/mm) print resolution

#### i Series™ Functionality:

- Automatic colour optimisation and driver configuration
- Enhanced ribbon formulation for optimal colour output
- Ribbon image counter and ribbon low notification
- Reduced media consumption with the monochrome ribbon-save mode

#### **BAR CODES**

- Code 39, Code 128 B & C with & without check digit
- 2 of 5 & 2 of 5 Interleaved
- UPC-A, EAN 8 & EAN 13
- PDF-417 2D bar code and other symbologies can be printed via Windows drivers



Software drivers for the Zebra P100i Card Printers are tested to ensure that they meet Microsoft® standards for Windows® compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries

#### CARD SPECIFICATIONS

- Types: PVC, PVC Composite
- · Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- Magnetic Stripe-ISO 7811
- Smart Card Contact and Contactless: 30 mil (.76mm) to 40 mil (1.02mm)
- · Card thickness: 20 mil (.508mm) to 40 mil (1.02mm)

#### **COMMUNICATIONS INTERFACE**

- USB 1.1 (USB 2.0 compatible) cable included
- Optional Built-in 10/100 Mbps Ethernet

#### **ELECTRICAL**

- 100 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- · 8MB image memory standard
- FCC Class A, CE, UL, CUL, and CCC approved

## RIBBON SPECIFICATIONS Ctrue COLOURS



- Load-N-Go™ ribbon cartridge
- i Series intelligent ribbon technology
- YMCKO: 200 cards/cartridge
- · Monochrome: 1000 cards/cartridge black, blue, green, gold, red, or silver. 850 cards/cartridge white

#### **PHYSICAL CHARACTERISTICS**

• Width: 7.9 in (201 mm) • Depth: 12.9 in (328 mm) • Height: 9.25 in (235 mm) • Weight: 10 lbs (4.5 kg)

For optimum printer performance use **Genuine Zebra Supplies** 

#### **ENVIRONMENTAL**

- Operating Temperature: 60°F to 86°F (15°C to 30°C)
- Operating Relative Humidity: 20% to 65% non-condensing
- Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- Storage Relative Humidity: 20% to 70% non-condensing
- · Ventilation: Free air

#### **OPTIONS**

- Built-in 10/100 Mbps Ethernet (factory installed)
- · Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- Smart Card Contact Encoder: ISO 7816 (EMV compliant)
- Smart Card Contactless Encoder: MIFARE®

#### **GENUINE ZEBRA SUPPLIES**

 Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.



\*Specifications subject to change without notice. ©2008 ZIH Corp. E3, QuickClip, ZBI 2.0, ZBI-Developer, ZebraDesigner, ZebraLink, ZebraNet and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head, Z-Band, ZebraNet, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. GS1 DataBar is a trademark of GS1 US, Inc. CG Triumvirate is a trademark of Monotype Imaging, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners

## THINKING ABOUT IMPROVING YOUR BUSINESS WITH ON-DEMAND **PRINTING SOLUTIONS?**

Zebra helps companies identify, locate and track assets, transactions and people with on-demand specialty digital printing and automatic identification solutions in more than 100 countries around the world.



To find out how your business could benefit from a Zebra solution, please visit www.zebra.com, call +44 (0)1628 556 000 or e-mail mseurope@zebra.com



Zebra Technologies - EMEA Headquarters Telephone: +44 (0)1628 556 000

E-mail: mseurope@zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East, Africa & India: Dubai, India, South Africa